



OS COLLECTION

Attractive, rugged and sonically accurate, the OS Collection of loudspeakers can be used in any outdoor environment to fill an area with beautiful sound. On the wall, attached to a pillar or under the eaves, sound can be projected across the deck or around the pool. High-performance drivers and passive radiators produce an impressive frequency response and allow homeowners to enjoy the same fidelity they experience inside the house.



OS67



OS65DT



OS65



OS57



OS55DT



OS55

AMP IT UP

High Performance Bass Augmented Outdoor Solution

DSP3-100 Amplifier

650 watts of DSP acoustic optimized performance

Bi-amplified for clean highs and tight bass

Expandable to (8) satellites



DSP3-100



OS65

SPECIFICATIONS

MODEL	OS67	OS65DT	OS65
PART	OCS6700B, OCS6700W	OCS6500DTB, OCS6500DTW	OCS6500B, OCS6500W
Woofers	4 x 8" Glass Fiber, 2 Passive Radiator	4 x 8" IMG, 2 Passive Radiator	4 x 8" IMG, 2 Passive Radiator
Tweeter	1" Aluminum	1" Dual Aluminum	1" Aluminum
Frequency Response	52Hz-20kHz	58Hz-20kHz	58Hz-20kHz
Power RMS	50 Watts	50 Watts	50 Watts
Power Peak	150 Watts	150 Watts	150 Watts
Impedance	6 ohm	6 ohm	6 ohm
Enclosure	HDPE	HDPE	HDPE
Grille	Aluminum	Aluminum	Aluminum
Dimensions	3 3/16 x 6 1/16 x 13 1/8" (182 x 172 x 334mm)	3 3/16 x 6 1/16 x 13 1/8" (182 x 172 x 334mm)	3 3/16 x 6 1/16 x 13 1/8" (182 x 172 x 334mm)

MODEL	OS57	OS55DT	OS55
PART	OCS5700B, OCS5700W	OCS5500DTB, OCS5500DTW	OCS5500B, OCS5500W
Woofers	5 1/4" Glass Fiber	5 1/4" IMG	5 1/4" IMG
Tweeter	3/4" Aluminum	Dual 3/4" Aluminum	3/4" Aluminum
Frequency Response	52Hz-20kHz	63Hz-20kHz	63Hz-20kHz
Power RMS	50 Watts	50 Watts	50 Watts
Power Peak	125 Watts	125 Watts	125 Watts
Impedance	6 ohm	6 ohm	6 ohm
Dimensions	3 3/16 x 6 1/16 x 13 1/8" (182 x 172 x 334mm)	3 3/16 x 6 1/16 x 10 13/32" (182 x 172 x 266mm)	3 3/16 x 6 1/16 x 10 13/32" (182 x 172 x 266mm)
Enclosure	HDPE	HDPE	HDPE
Grille	Aluminum	Aluminum	Aluminum

