

SOUNDBARS

SPECS

SPECIFICATION

Woofers	3 1/2" Fiber Glass
Tweeter	1" Silk DPSD™
Frequency Response	65Hz - 20kHz
Impedance	4 Ω per Channel
Power RMS	75 Watts
Power Peak	150 Watts
Sensitivity	90 dB
Enclosure	Aluminum Cabinet

ALL MODELS

MODEL

CHANNELS

SBR41	1
SBR41-LCR	1
SBR43-50	3
SBR43-55	3
SBR43-60	3
SBR43-65	3
SBR43-70	3
SBR43-75	3
SBR43-80	3
SBR43-85	3

SBR41



SBR41-LCR



SBR43-55



SBR43-75





MODEL	PART	DIMENSIONS
SBR41	SBR41000	11 ⁵⁷ / ₆₄ " L x 6" H x 2 ⁹ / ₁₆ " D [302 L x 152 H x 65 D mm]
SBR41-LCR	SBR41LCR	16 ⁷ / ₆₄ " L x 6" H x 2 ⁹ / ₁₆ " D [409 L x 152 H x 65 D mm]
SBR43-50	SBR43500	42 ¹ / ₈ " L x 6" H x 2 ⁹ / ₁₆ " D [1070 L x 152 H x 65 D mm]
SBR43-55	SBR43550	48 ¹⁵ / ₆₄ " L x 6" H x 2 ⁹ / ₁₆ " D [1225 L x 152 H x 65 D mm]
SBR43-60	SBR43600	52 ²³ / ₃₂ " L x 6" H x 2 ⁹ / ₁₆ " D [1339 L x 152 H x 65 D mm]
SBR43-65	SBR43650	56 ¹ / ₂ " L x 6" H x 2 ⁹ / ₁₆ " D [1435 L x 152 H x 65 D mm]
SBR43-70	SBR43700	60 ⁵³ / ₆₄ " L x 6" H x 2 ⁹ / ₁₆ " D [1545 L x 152 H x 65 D mm]
SBR43-75	SBR43750	65 ⁵ / ₃₂ " L x 6" H x 2 ⁹ / ₁₆ " D [1655 L x 152 H x 65 D mm]
SBR43-80	SBR43800	69 ³¹ / ₆₄ " L x 6" H x 2 ⁹ / ₁₆ " D [1765 L x 152 H x 65 D mm]
SBR43-85	SBR43850	74 ¹ / ₆₄ " L x 6" H x 2 ⁹ / ₁₆ " D [1880 L x 152 H x 65 D mm]

Please visit docs.originacoustics.com or scan the QR code using your smart device for the most up to date safety information and use instructions for this product.



*All warranties and warranty conditions are subject to change. Please refer to docs.originacoustics.com for the latest information.