ORIGIN ACOUSTICS

EXPLORER COLLECTION

LUXURY SOUND ON WATER OR LAND BY ORIGIN ACOUSTICS



C65EX



D105EX D85EX D83EX D83AEX D83DT/SUREX





CSUB10REX
SUBWOOFER



D80-8EX (8-PACK) D65EX D60-8EX (8-PACK) D55EX



DBA10EX
SUBWOOFER

DBA5EX
SUBWOOFER



TRAVEL THE SEVEN SEAS WITH THE NEW EXPLORER COLLECTION

The Explorer Collection of loudspeakers from Origin Acoustics were developed to withstand the harsh conditions found in marine environments. This includes exposure to saltwater, extreme temperature changes and airborne humidity. They will produce amazing musical fidelity while spending family time on the lake or a trip on the open sea and they have the build quality to last for years in these situations.

Utilizing a unique weatherproof coating, careful attention has been taken to protect every component in the speaker system from the electro-mechanical driver elements to the crossover networks. Stainless steel fasteners and connectors are selected to enhance wire connections and overall system durability. Now you can experience the incredible sound quality we are known for while enjoying your time on the water.

IN-CEILING SPEAKERS

SPECIFICATIONS	D105EX	D85EX	D83EX	D83AEX
Part	SCD100500EX	SCD85000EX	DSC83000EX	SCD08030AEX
Woofer	10” IMG	8” IMG	8” IMG	8” IMG - Pre-Angled Graphite
Midrange	4” Graphite Pivoting	4” IMG MMP	-	-
Tweeter	¾” Aluminum MMP™	1” Aluminum MMP	1” Aluminum MMP	1” Aluminum
Frequency Response	28 Hz - 20 kHz	36Hz-20kHz	38Hz-20kHz	38Hz-20kHz
Power RMS	50W-150W	50W-150W	50W-150W	50W-150W
Impedance	6 ohm	6 ohm	6 ohm	6 ohm
Mounting Depth	**6 3/16”(158mm)**	**5 5/8” (142mm)**	**4 1/2” (114mm)**	**4 11/16” (119mm)**

IN-CEILING SPEAKERS

SPECIFICATIONS	D83DT/SUREX	D80-8EX (8-PACK)	D65EX	D60-8EX (8-PACK)
Part	SCDT83000EX	SCD80000	SCD65000EX	SCD60000
Woofer	8” IMG	8” Poly/Rubber	6 ½” IMG Pivoting	6 ½” Poly/Rubber
Midrange	-	-	-	-
Tweeter	Dual 1” Aluminum	1” Silk Pivoting	1” Aluminum MMP	1” Silk Pivoting
Frequency Response	38Hz-20kHz	40Hz-20kHz	45Hz-20kHz	50Hz-20kHz
Power RMS	50W-150W	40W-100W	40W-150W	40W-100W
Impedance	6 ohm	6 ohm	6 ohm	6 ohm
Mounting Depth	**4 5/16” (109mm)**	**4 5/16” (109mm)**	**5 1/4” (134mm)**	**3 5/8” (92mm)**

IN-CEILING SPEAKERS

SPECIFICATIONS	D55EX
Part	SCD50500EX
Woofer	5 ¼” IMG
Midrange	-
Tweeter	1” Aluminum MMP
Frequency Response	83Hz-20kHz (-3dB)
Power RMS	30W - 100W
Impedance	6 ohm
Mounting Depth	**3 ½” (90mm)**

IN-CEILING SUBWOOFERS

DBA10EX SUBWOOFER	DBA5EX SUBWOOFER
DBA1000EX	DBA5000EX
10” Glass Fiber	5 ¼” Glass Fiber
-	-
-	-
35Hz – 200Hz	39Hz-200Hz (-10dB)
50W- 150W	30W-100W
6 ohm	4 ohm
6 3/16” (158 mm)	**3 ¾” (95mm)**

IN-WALL SPEAKER

SPECIFICATIONS	C65EX
Part	SWM12500REX
Woofer	4 x 8” IMG
Midrange	-
Tweeter	1” Aluminum
Frequency Response	45Hz-20kHz
Power RMS	50W- 125W
Impedance	8 ohm
Cut -Out Dimensions	4⅝” W x 11” H (118 x 278mm)
Mounting Depth	**3 ¾” (95mm)**

IN-WALL SUBWOOFER

CSUB10REX SUBWOOFER
CSUB1000REX
10” Black, Anodized Aluminum
-
-
30Hz-250Hz
100-500 W
8 ohm
13 ⅛” W x 13 ⅛” H (333 W x 333 H mm)
3 ½” (90mm)

IC SPEAKERS	**Cutout Diameter**
All 10” Explorers	10 3/8” (264mm)
All 8” Explorers	8 ¾” (222mm)
All 6” Explorers	8 ¾” (222mm)
All 5” Explorers	5 ⅞” (150mm)

Find out more at originacoustics.com

05-05-25

 ©2025 Origin Acoustics. All copyrighted, trademarked and patented elements mentioned herein are the sole property of Origin Acoustics | 2025